North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

# MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

#### [ ] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

#### [X] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

#### [ ] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

#### [ ] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Behr Process Corporation

Product Name: 61 Acoustic Patch Old White (DISCONTINUED)

### MATERIAL SAFETY DATA SHEET

61 ACOUSTIC PATCH OLD WHITE

Page: 1

PRODUCT NAME: 61 ACOUSTIC PATCH OLD WHITE

PRODUCT CODE: 006199-10301

HMIS CODES: H F R P 1 0 0 E

ARREST SECTION I - MANUFACTURER IDENTIFICATION SEGRET SECTION SEGRET SECTION S

MANUFACTURER'S NAME: BEHR PROCESS CORPORATION

ADDRESS : 3400 GARRY AVE.

SANTA ANA, CA 92704

EMERGENCY PHONE : (800) 424-9300 DATE PRINTED : 04/28/00 INFORMATION PHONE : (714) 545-7101 NAME OF PREPARER : Mike Butler

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

Vapor pressure weiget Offerts cas burger as by 6 temp percent

REPORTABLE COMPONENTS CAS WINGER. 200 Rg 0 TEMP PERCENT

\* indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 0.79
VAPOR DENSITY: Heavier than air EVAPORATION RATE: Equal to water.

COATING V.O.C.: 4 g/1 MATERIAL V.O.C.: 4 g/1

SOLUBILITY IN WATER: Infinite.

APPEARANCE AND ODOR: Pigmented liquid with a sweet ammoniacal odor.

FLASH POINT: N/A METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: Foam, Alcohol Foam CO2 Dry Chemical Water Fog

SPECIAL FIREFIGHTING PROCEDURES

Observe recommended procedures in handling fire areas. Wear appropriate fire fighting equipment including a self-contained breathing apparatus

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers are subject to bursting on exposure to heat Extinguishing media above is recommended on dried films of this material that is burning. This material is non-combustable, but dried films are capable of burning and supporting combustion when contact with open flames.

FLAMMABILITY - T.D.G.R. CLASS

DOT Not Regulated

OSHA AND NFPA COMBUSTIBLE LIQUID CLASS IIIB

SENSITIVITY TO IMPACT

None known

SENSITIVITY TO STATIC DISCHARGE

None expected

# MATERIAL SAFETY DATA SHEET

#### 61 ACOUSTIC PATCH OLD WHITE

Page: 2

STABILITY: Stable.
CONDITIONS TO AVOID

Avoid freezing - Avoid temperatures below 32 degrees F

### INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid highly oxidizing materials - Avoid materials that react with water - Also avoid strong acids and alkalines

## HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Incomplete combustion can lead to the evolution of Carbon Dioxide and/or Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

# SECTION VI - HEALTH HAZARD DATA SECTION VI - HEALTH HAZARD DATA

## INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

## SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

## SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Not absorbed into skin May cause minor redness and/or irritation

## INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Marmful of swallowed Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation

## HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute Health Hazards Repeated skin contact may result in the development of an allergic skin reaction in a small number of individuals

Chronic Health Hazards None known

CARCINOGENICITY: NTP CARCINOGEN: Product is not a known carcinogen

IARC MONOGRAPHS: NO OSHA REGULATED: NO

# MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Available toxicology, chemical and physical data show that overexposure is unlikely to aggravate any medical condition

### EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT Flush with water for 15 minutes Expose to fresh air Call Physician immediately

SKIN CONTACT Wash with soap and water for 15 minutes

IMPALATION Remove to fresh air Call physician if experiencing any difficulty breathing

INGESTION DO NOT INDUCE VOMITING! CALL PHYSICIAN IMMEDIATELY Activated charcoal may be administered 
If conscious, feed two glasses of water

# SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

# STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike and/or absorb spilled material with inert absorbant material such as sand or sawdust. Use rags to clean up small amounts of spilled materials. Keep out of sewers, watersheds or water systems.

#### WASTE DISPOSAL METHOD

PRODUCT DISPOSAL Product does not meet the definition of hazardous waste under the U.S. E.P.A. regulations However state or local

### MATERIAL SAPETY DATA SHEET

#### 61 ACOUSTIC PATCH OLD WHITE

Page:

3

hazardous waste regulations may apply if they are different from the federal regulations

CONTAINER DISPOSAL Triple rings container, then dispose of in a sanitary landful, if allowed by local regulation

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers closed when not in use. Do not store or handle near heat, flames or strong oxidants. Store in cool, well ventilated areas. Rotate stock to use older material first. Inspect for leaks or cracks in all containers.

#### OTHER PRECAUTIONS

SECTION VIII - CONTROL MEASURES SECRESERERERERERERE

#### RESPIRATORY PROTECTION

Wear approved NIOSH/MSHA respirator with organic vapor cartridge when the environmental controls are inadequate at keeping the airborne concentrations below the exposure levels

#### VENTILATION

General mechanical ventilation may be sufficient to keep product vapor concentrations below the specified TLV levels. If adequate, one can also use local exhaust

#### PROTECTIVE GLOVES

Use solvent impermeable Neoprene or latex gloves to protect against skin contact

#### EYE PROTECTION

Use safety goggles safety glasses and/or face shields to protect the eyes

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Impermeable aprons or protective clothing are recommended when working with this product. The use of head caps are also recommended whenever possible

#### WORK/HYGIENIC PRACTICES

Care should be taken to prevent unnecessary exposure to this product. Eye washes and safety showers should be available

DEDUCATION OF THE PROPERTY OF

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originated with the company or not Since the use of this information and the conditions of use are not within the control of the manufacturer, it is the user's obligation to determine the conditions for safe use of this product. All ingredients used in the manufacture of this product are if required, listed on the TSCA inventory.